

FEATURES INSTALLATION

PRODUCT		TERAGRI	EN XCORA® STRAND	BAMB00	TERAGREN PUREFORM™ BAMBOO					
	Portfolio TG Collection	Synergy® Wide Plank	Synergy [®] MPL	Synergy® One	Vantage II	Studio	Craftsman II	Signature Collection	Elements	
Hardness Rating			160% Harder Than Oak		40% Harder Than Oak					
Nominal Dimensions (LxWxD")	72.44" x 5.43" x 0.47"	72.05" x 7.68" x 0.55"	24, 36, 48 & 72" x 3.78" x 0.47"	72" x 3.78" x 0.47"	72.83" x 5.59" x 0.55"	75" x 7.68" x 0.55"	75.59" x 5.43" x 0.59"	24, 36, 48 & 72.44" x 3.62" x 0.59"	36.22" x 3.62" x 0.59"	
mm Profile*	12 mm	14 mm	12 mm	12 mm	14 mm	14 mm	15 mm	15 mm	15 mm	
Construction	Solid	Engineered	Solid	Solid	Engineered	Engineered	Solid	Solid	Solid	
Width	Wide Plank	Extra Wide Plank	Narrow Plank	Narrow Plank	Wide Plank	Extra Wide Plank	Wide Plank	Narrow Plank	Narrow Plank	
Length	Single Long-Length	Single Long-Length	Multiple Precise Lengths	Single Long-Length	Single Long-Length	Single Long-Length	Extra Long-Length	Multiple Precise Lengths	3 Foot Lengths	
Milling	Micro-bevel	Square-edge	Micro-bevel	Micro-bevel	Eased-edge	Square-edge	Micro-bevel	Micro-bevel	Micro-bevel	
Profile	Tongue + Groove	Self-locking	Tongue + Groove	Tongue + Groove	Tongue + Groove	Self-locking	Tongue + Groove	Tongue + Groove	Tongue + Groove	
Color Variation	Moderate	Moderate	Moderate	Moderate	Moderate	High	Moderate	Moderate	High	
Square Feet per Box	21.87	23.05	22.69	22.69	28.28	23.99	28.52	21.86	18.22	
USDA BioPreferred	1	1	1	✓		1	1	1	1	
Indoor Air Quality Rating	Floorscore	Floorscore	Floorscore	Floorscore	CA 01350	Floorscore	Floorscore	Floorscore	Floorscore	
FSC® Certified					1	**	**	**	**	
LEED® IEQ 4.3 Low Emitting Materials	1	1	1	✓	1	1	1	1	1	
LEED® MR6 Rapidly Renewable Resource	1	1	✓	✓	1	1	1	1	1	
LEED® MR7 Certified Wood					1	**	**	**	**	
CA High Performance Schools EQ2.2.3	1	1	1	✓	1	1	1	1	1	
Coordinating Accessories		Full Line of Coordinating Stair Parts & Accessories								
Warranty *Determines coordination	,	· 	Finish Warranty; Lifetime Struc	·	25-year Residential & 10-year Commercial Finish Warranty; Lifetime Structural Warranty					

^{*}Determines coordinating accessories

^{**} Available by special order (minimum quantities apply)



FEATURES		INSTALLATIO	N							
PRODUCT	TERAGREN XCORA® STRAND BAMBOO					TERAGREN PUREFORM™ BAMBOO				
	Portfolio TG Collection	Synergy [©] Wide Plank	Synergy [®] MPL	Synergy® One	Vantage II	Studio	Craftsman II	Signature Collection	Elements	
Float - On/Above or Below grade	✓	1			✓	✓	1			
Nail - On/ Above grade	✓		✓	✓	✓		✓	✓	1	
Staple - On/ Above grade					1		1	1	1	
Glue - On/ Above grade*	✓		✓	✓	✓		✓	1	✓	
			NOTE: Re	commended Adhesive - P	remium Bamboo Flooring A	dhesive				
Underlayment	A, B, C	A	В, С	В, С	А, В, С	A	А, В, С	В, С	В, С	
Nailing Guidelines	A	Not Applicable	В	В	C	Not Applicable	D	D	D	
Radiant Floor Compliant	Can be installed over radiant heat									
Acclimation	Minimum of 48 hours on-site in box									
Site RH	Install into environments having 35-55% Relative Humidity									
Maintenance	Rubio Monocoat: Surface Care Soap, Refresh Spray Oil, Maintenance Oil							al		

Underlayment:

- A Float: Vapor barrier with pad over cement subfloor, vapor retarder with pad over wood subfloor
- B Nail/Staple: Vapor retarder over wood subfloor
- C Glue: Vapor barrier over cement subfloor, vapor retarder over wood subfloor

Nailing Guidelines:

- A 18 gauge cleat 1½"-2"
- B 18 gauge cleat 11/4" 11/2"
- C 18 gauge cleat or narrow crown staple 11/4" to 11/2"
- D 15-16 gauge cleat or staple 11/2"-2"