SYNERGY® ONE

Solid-strip Xcora[™] strand bamboo flooring



FINE BAMBOO FLOORING, PANELS & WORKTOPS

One classic length in Teragren's best selling solid-strip profile combined with our Xcora™ strand bamboo. Designed for use in commercial and residential interiors.



FEATURES + BENEFITS

PERFORMANCE

- Durable 9-step UV Cured Polyurethane coating system with aluminum oxide wear layer for abrasion resistance
- Premium solid-stock Xcora strand bamboo in a classic long length 160% harder than
- Optimum 5.5 Moso Bamboo: Harvested at maturity for peak density, creating a harder and more stable product for lasting beauty and performance
- Approved for installation over radiant heat flooring systems.

• Lifetime structural warranty; 10-year heavy-use commercial/25-year residential finish warranties

ECOSMART

Certified USDA BioPreferred – 94% biobased content

INDOOR AIR QUALITY

- Floorscore certified for superior indoor air quality.
- Qualifies for Collaborative for High Performance Schools 2009 Criteria EQ2.2.3 Low **Emitting Materials**

PRODUCT DETAILS

Nominal Dimensions: 72" x 3.78" x 0.47"

Solid Xcora™ Strand Bamboo Construction:

Milling: 4 side micro-bevel Tongue and groove Profile:

Full line of coordinating 12mm accessories Accessories: Finish Warranty: 25-year residential /10-year commercial

Structural Warranty: Lifetime

Hardness Rating: 3271 Janka rating; 160% harder than oak

Moderate Color Variation:

INSTALLATION + CARE

Nail/Glue Installation: On or above grade

Underlayment: Nail: Vapor retarder; Glue: Vapor barrier over cement or vapor retarder

over wood

Recommended Adhesive: **Premium Wood Flooring Adhesive**

18 ga cleat 1 ¼" – 1 ½" Nailing Guidelines: Acclimation: 48 hours on-site in box

Maintenance: BonaKemi Pro Series Hardwood Floor Cleaner or equal



LEED® CREDITS

- IEQ 4.3 Low Emitting Materials
- MR6 Rapidly Renewable Materials





Brindle